

COSMOFEN 345 ADHESIVE

MSDS Preparation Date (dd/mm/yyyy): 01/03/2010

Page 1 of 8

MATERIAL SAFETY DATA SHEET

SECTION 1 - IDENTIFICATION

Product identifier : **COSMOFEN 345 ADHESIVE**

Product Code(s) : Adhesive.

Product Use : Adhesive used in PVC window construction.

Chemical Family : Mixture.

Supplier's name and address:
Ferco Ferrures de bâtiment
2000, rue Berlier
Laval, QC, Canada
H7L 4S4

Manufacturer's name and address:
Refer to Supplier

Information Telephone # : (514) 973-1437

24 Hr. Emergency Tel # : Not available.

SECTION 2 - HAZARDS IDENTIFICATION

Classification : WHMIS information: This product is a WHMIS Controlled Product. It meets one or more of the criteria for a controlled product provided in Part IV of the Canadian Controlled Products Regulations (CPR). WHMIS classification:
Class B2 (Flammable Liquids);
Class D2A (Materials Causing Other Toxic Effects, Very Toxic Material);
Class D2B (Materials Causing Other Toxic Effects, Toxic Material).

OSHA: This material is classified as hazardous under OSHA regulations (29CFR 1910.1200). Hazardous classification:
Flammable liquid;
Acute Health Hazard;
Chronic Health Hazard.

Emergency Overview : Paste. Various colours. Characteristic odour.
WARNING! Flammable liquid. Vapour may cause flash fire! May be harmful if inhaled. May cause nausea, vomiting, headache and other central nervous system effects. May be fatal if swallowed - can enter the lungs and cause damage. IRRITANT. Causes eye irritation. May cause skin irritation. May cause respiratory irritation. Possible birth defect hazard - contains material that may cause birth defects, based on animal data. Possible reproductive hazard. Contains material that may cause adverse reproductive effects, based on animal data. Possible cancer hazard - contains material which may cause cancer.

POTENTIAL HEALTH EFFECTS:

Signs and symptoms of short-term (acute) exposure

Inhalation : May cause irritation to the nose, throat and upper respiratory tract. Symptoms may include pain, headache, nausea, vomiting, dizziness, drowsiness and other central nervous system effects. Could result in pulmonary edema (fluid accumulation). Symptoms of pulmonary edema (chest pain, shortness of breath) may be delayed.

Skin : May cause mild to moderate skin irritation. Product may be absorbed.

Eyes : May cause moderate to severe irritation. Symptoms will include pain, redness and tearing.

Ingestion : May cause irritation of mouth, throat, and stomach. Symptoms may include pain, headache, nausea, vomiting, dizziness, drowsiness and other central nervous system effects. May be an aspiration hazard. Aspiration into the lungs during swallowing or subsequent vomiting may cause chemical pneumonitis, which can be fatal.

Effects of long-term (chronic) exposure

: Prolonged or repeated contact may cause drying, cracking and defatting of the skin. Prolonged overexposure may cause liver and kidney effects.

Carcinogenic status : See TOXICOLOGICAL INFORMATION, Section 11.

Additional health hazards : Potential teratogen. Potential reproductive toxicant. See TOXICOLOGICAL INFORMATION, Section 11.

COSMOFEN 345 ADHESIVE

MSDS Preparation Date (dd/mm/yyyy): 01/03/2010

Page 2 of 8

Potential environmental effects

: See ECOLOGICAL INFORMATION, Section 12.

SECTION 3 - COMPOSITION/INFORMATION ON INGREDIENTS

<u>Ingredients</u>	<u>CAS #</u>	<u>Wt.%</u>
Methy ethyl ketone	78-93-3	30.00 - 50.00
Diisobutyl phthalate	84-69-5	1.00 - 5.00
Xylene	1330-20-7	10.00 - 15.00
The following components are only present as part of the Xylene ingredient:		
Ethylbenzene	100-41-4	1.00 - 5.00

Note: Ethylbenzene is not intentionally added to this product.

SECTION 4 - FIRST AID MEASURES

- Inhalation** : Remove exposed person to fresh air immediately. If breathing is difficult, give oxygen by qualified medical personnel only. If breathing stopped, begin artificial respiration. Get medical attention.
- Skin contact** : Remove contaminated clothing and shoes under running water. Wash affected areas with soap and water. If skin irritation or rash occurs, seek medical advice/attention. Wash contaminated clothing before reuse.
- Eye contact** : Immediately flush eyes with plenty of water for at least 15 minutes. Seek immediate medical attention/advice.
- Ingestion** : Never give anything by mouth to an unconscious person. Do NOT induce vomiting. If vomiting occurs spontaneously, keep victim's head lowered (forward) to reduce the risk of aspiration. Obtain medical attention immediately.
- Notes For Physician** : Treat symptomatically. This product is a CNS depressant.

SECTION 5 - FIRE FIGHTING MEASURES

Fire hazards/conditions of flammability

- : Flammable liquid. Vapours may form explosive mixture with air. Closed containers may rupture if exposed to excess heat or flame due to a build-up of internal pressure. Product may float, and be re-ignited at the water's surface.

Flammability classification (OSHA 29 CFR 1910.1200)

- : Flammable Liquid Class 1B.

Oxidizing properties

- : None known.

Explosion data: Sensitivity to mechanical impact / static discharge

- : Not expected to be sensitive to mechanical impact. Product will accumulate static charge. Mixtures of vapour and air at concentrations in the flammable range may be ignited by a static discharge of sufficient energy.

- Suitable extinguishing media** : Dry chemical, carbon dioxide and foam. Do not use water jet, as this may spread burning material.

Special fire-fighting procedures/equipment

- : During a fire, irritating and toxic gases may be generated by thermal decomposition or combustion. Do not enter fire area without proper protection. Firefighters should wear proper protective equipment and self-contained breathing apparatus with full face piece operated in positive pressure mode. Move containers from fire area if safe to do so. Water spray may be useful in cooling equipment exposed to heat and flame.

Hazardous combustion products

- : Carbon oxides; Aldehydes; Hydrocarbons; nitrogen oxides (NOx); other unidentified organic compounds.

NFPA Rating

0 - Minimal	1 - Slight	2 - Moderate	3 - Serious
<i>Health: 2</i>	<i>Flammability: 3</i>	<i>Instability: 0</i>	<i>Special Hazards: None</i>

COSMOFEN 345 ADHESIVE

MSDS Preparation Date (dd/mm/yyyy): 01/03/2010

Page 3 of 8

SECTION 6 - ACCIDENTAL RELEASE MEASURES

- Personal precautions** : Restrict access to area until completion of clean-up. Ensure clean-up is conducted by trained personnel only. All persons dealing with clean-up should wear the appropriate protective equipment including self-contained breathing apparatus. Refer to Section 8, EXPOSURE CONTROLS AND PERSONAL PROTECTION, for additional information on acceptable personal protective equipment.
- Environmental precautions** : Do not allow material to contaminate ground water system. Dispose of as special waste in compliance with local and national regulations.
- Spill response/cleanup** : Ventilate area of release. Eliminate all ignition sources. Remove combustible materials. Stop the spill at source if it is safe to do so. Use only non-sparking tools and equipment in the clean-up process. Contain and absorb spilled liquid with non-combustible, inert absorbent material (e.g. sand), then place absorbent material into a container for later disposal (see Section 13). Contaminated absorbent material may pose the same hazards as the spilled product. Notify the appropriate authorities as required.
- Prohibited materials** : Do not use combustible absorbents, such as sawdust.
- Special spill response procedures** : If a spill/release in excess of the EPA reportable quantity is made into the environment, immediately notify the national response center in the United States (phone: 1-800-424-8002).
US CERCLA Reportable quantity (RQ): methyl ethyl ketone (5000 lbs / 2270 kg); Xylene (100 lbs / 45.4 kg); Ethylbenzene (1000 lbs / 454 kg).

SECTION 7 - HANDLING AND STORAGE

- Safe Handling procedures** : Before handling, it is very important that engineering controls are operating, and that protective equipment requirements and personal hygiene measures are being followed. People working with this chemical should be properly trained regarding its hazards and its safe use. Bond and ground transfer containers and equipment. Do not use near welding operations, flames or hot surfaces. Inspect containers for leaks before handling. Label containers appropriately. Ensure adequate ventilation. Avoid breathing vapour or mist. Avoid contact with skin, eyes and clothing. Keep away from heat, sparks, and open flames. Prevent buildup of vapours. Keep away from oxidizing agents and incompatibles. Keep containers closed when not in use. Empty containers retain residue (liquid and/or vapour) and can be dangerous.
- Storage requirements** : Store in a cool, dry, well ventilated area, away from heat and ignition sources. Store out of direct sunlight. Do not store near any incompatible materials (see Section 10). Inspect all incoming containers to make sure they are properly labelled and not damaged. Keep container tightly closed. Storage facilities should be made of fire resistant materials. For large-scale storage, use a grounded, non-sparking ventilation system, approved explosion-proof equipment and intrinsically safe electrical systems. Storage area should be clearly identified, clear of obstruction and accessible only to trained and authorized personnel. Inspect periodically for damage or leaks. Have appropriate fire extinguishers and spill clean-up equipment in or near storage area. Average Shelf Life: 12 months (when stored in original, unopened, sealed containers).
Recommended storage temperature: 15 - 25°C (59 - 77°F).
- Incompatible materials** : Oxidizing agents; Acids; Bases; Halogenated compounds.
- Special packaging materials** : Always keep in containers made of the same materials as the supply container.

SECTION 8 - EXPOSURE CONTROLS AND PERSONAL PROTECTION

COSMOFEN 345 ADHESIVE

MSDS Preparation Date (dd/mm/yyyy): 01/03/2010

Page 4 of 8

Exposure Limits				
Ingredients	ACGIH TLV		OSHA PEL	
	TWA	STEL	PEL	STEL
Methy ethyl ketone	200 ppm	300 ppm	200 ppm	N/Av
Diisobutyl phthalate	N/Av	N/Av	N/Av	N/Av
Xylene	100 ppm	150 ppm	100 ppm	N/Av
The following components are only present as part of the Xylene ingredient:				
Ethylbenzene	100 ppm	125 ppm	100 ppm	N/Av

Ventilation and engineering measures

: Local exhaust ventilation is preferred to prevent contaminant dispersion into work area.

Respiratory protection

: Respiratory protection is required if the concentrations exceed the TLV. NIOSH-approved respirators are recommended.

Skin protection

: Wear chemically protective gloves (impervious), boots, aprons, and gauntlets to prevent prolonged or repeated skin contact.

Eye / face protection

: Wear protective chemical safety goggles, or in splash environment, in combination with a face shield.

Other protective equipment

: Depending on conditions of use, safety shoes and additional protective clothing may also be necessary. An eyewash station and safety shower should be made available in the immediate working area.

General hygiene considerations

: Avoid contact with skin, eyes and clothing. Avoid breathing vapour or mist. Do not eat, drink, smoke or use cosmetics while working with this product. Handle in accordance with good industrial hygiene and safety practice. Remove and wash contaminated clothing before re-use. Separate contaminated work clothes from street clothes.

SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES

Physical state	: paste	Appearance	: Various colours.
Odour	: characteristic	Odour threshold	: N/Av
pH	: N/Av		
Boiling point	: N/Av	Specific gravity	: 1.01
Melting/Freezing point	: N/Av	Coefficient of water/oil distribution	: N/Av
Vapour pressure (mmHg @ 20° C / 68° F)	: N/Av	Solubility in water	: Insoluble.
Vapour density (Air = 1)	: N/Av	Evaporation rate (n-Butyl acetate = 1)	: N/Av
Volatile organic Compounds (VOC's)	: N/Av	Volatiles (% by weight)	: N/Av
Flash point	: - 4°C (25°F)		
Flash point Method	: Not reported	Auto-ignition temperature	: 400°C (752°F)
Lower flammable limit (% by vol.)	: N/Av	Upper flammable limit (% by vol.)	: N/Av
Flame Projection Length	: N/Av	Flashback observed	: N/Av

Section 10: Stability And Reactivity

Stability and reactivity : Stable under the recommended storage and handling conditions prescribed. May form explosive peroxides during prolonged exposure to air and heat. Hydrolyzes slowly under weak alkaline or acidic conditions.

Hazardous polymerization : Hazardous polymerisation does not occur.

Conditions to avoid : Avoid heat, open flames, sparks, static electricity and electrical equipment. Keep away from direct sunlight.

COSMOFEN 345 ADHESIVE

MSDS Preparation Date (dd/mm/yyyy): 01/03/2010

Page 5 of 8

Materials To Avoid And Incompatibility

: See Section 7 (Handling and Storage) for further details.

Hazardous decomposition products

: Peroxides. Refer to Section 5 for additional 'Hazardous combustion products'.

SECTION 11 - TOXICOLOGICAL INFORMATION

Target organs : Eyes, skin, respiratory system, digestive system, central nervous system. Liver; Kidneys.

Routes of exposure : *Inhalation:* YES *Skin Absorption:* YES *Skin & Eyes:* YES *Ingestion:* YES

Toxicological data : There is no available data for the product itself, only for the ingredients. See below for individual ingredient acute toxicity data.

<u>Ingredients</u>	<u>LC₅₀(4hr)</u> <u>inh, rat</u>	<u>LD₅₀</u>	
		<u>(Oral, rat)</u>	<u>(Rabbit, dermal)</u>
Methy ethyl ketone	11,300 ppm	2740 mg/kg	6480 mg/kg
Diisobutyl phthalate	N/Av	10,400 mg/kg	N/Av
Xylene	6350ppm	4300 mg/kg	12,180 mg/kg
The following components are only present as part of the Xylene ingredient:			
Ethylbenzene	4000 ppm	3500 mg/kg	15,380 mg/kg

Carcinogenic status : Contains Ethylbenzene. Ethylbenzene is classified as carcinogenic by IARC (Group 2B) and ACGIH (Category A3). Ethylbenzene is a component of Xylene.

Reproductive effects : Contains Diisobutyl phthalate. Diisobutyl phthalate may cause adverse effects on the male reproductive system, based on animal data.

Teratogenicity : POSSIBLE BIRTH DEFECT HAZARD. This product contains Xylene. Xylene may cause fetotoxic effects at doses which are not maternally toxic, based on animal data. Contains Diisobutyl phthalate. Diisobutyl phthalate is a teratogen.

Mutagenicity : None known.

Epidemiology : Not available.

Sensitization to material : Not expected to be a skin or respiratory sensitizer.

Synergistic materials : None known or reported by the manufacturer. Exposure to related solvents, such as benzene, toluene and ethanol (alcohol) slows the rate of clearance of Xylene from the body, thus enhancing its toxic effects. Exposure to Xylene in combination with other solvents has had an additive effect with respect to harming the hearing of rats.

Irritancy : Mild to moderate skin irritant. Moderate to severe eye irritant.

other important hazards : CNS depression may result from extreme exposures.

Conditions aggravated by overexposure

: Pre-existing skin, eye and respiratory disorders.

SECTION 12 - ECOLOGICAL INFORMATION

Ecotoxicity : No data is available on the product itself. The product should not be allowed to enter drains or water courses, or be deposited where it can affect ground or surface waters.

Mobility : No data is available on the product itself.

Persistence : No data is available on the product itself.

Bioaccumulation potential : No data is available on the product itself.

Other Adverse Environmental effects

: No data is available on the product itself.

SECTION 13 - DISPOSAL CONSIDERATIONS

Handling for Disposal : Store material for disposal as indicated in Handling and Storage (Section 7). Empty containers retain residue (liquid and/or vapour) and can be dangerous. Do not cut, weld, drill or grind on or near this container.

COSMOFEN 345 ADHESIVE



MSDS Preparation Date (dd/mm/yyyy): 01/03/2010

Page 6 of 8

Methods of Disposal : Dispose in accordance with all applicable federal, state, provincial and local regulations. Contact your local, state, provincial or federal environmental agency for specific rules.

RCRA : If this product, as supplied, becomes a waste in the United States, it may meet the criteria of a hazardous waste as defined under RCRA, Title 40 CFR 261. It is the responsibility of the waste generator to determine the proper waste identification and disposal method. For disposal of unused or waste material, check with local, state and federal environmental agencies.

SECTION 14: TRANSPORT INFORMATION

Regulatory Information	UN Number	Shipping Name	Class	Packing Group	Label
TDG	UN1133	ADHESIVES	3	II	
TDG Additional information	May be shipped as Limited Quantity when transported in containers no larger than 5.0 Litres; in packages not exceeding 30 kg gross mass. Under the TDGR, refer to Section 1.17 for additional exemption information, if shipping under this exemption.				
49CFR/DOT	UN1133	Adhesives	3	II	
49CFR/DOT Additional information	May be shipped as Limited Quantity when transported in containers no larger than 5.0 Litres; in packages not exceeding 30 kg gross mass. Refer to 49 CFR 173.150(b) and Special Provision 149.				

SECTION 15 - REGULATORY INFORMATION

US Federal Information:

TSCA: All listed ingredients appear on the Toxic Substances Control Act (TSCA) inventory.

CERCLA Reportable Quantity (RQ) (40 CFR 117.302): methyl ethyl ketone (5000 lbs / 2270 kg); Xylene (100 lbs / 45.4 kg); Ethylbenzene (1000 lbs / 454 kg).

SARA TITLE III: Sec. 302, Extremely Hazardous Substances, 40 CFR 355: No Extremely Hazardous Substances are present in this material.

SARA TITLE III: Sec. 311 and 312, MSDS Requirements, 40 CFR 370 Hazard Classes: Fire Hazard; Immediate (Acute) health hazard; Chronic Health Hazard. Under SARA Sections 311 and 312, the EPA has established threshold quantities for the reporting of hazardous chemicals. The current thresholds are 500 pounds for the threshold planning quantity (TPQ), whichever is lower, for extremely hazardous substances and 10,000 pounds for all other hazardous chemicals.

SARA TITLE III: Sec. 313, Toxic Chemicals Notification, 40 CFR 372: This product may be subject to SARA notification requirements, since it contains Toxic Chemical constituents above their de minimus concentrations. This product contains: Xylene; Ethylbenzene.

US State Right to Know Laws:

California Proposition 65: This product contains a chemical known to the State of California to cause cancer. Contains: Ethylbenzene.

Other U.S. State "Right to Know" Lists: The following chemicals are specifically listed by individual States: methyl ethyl ketone (CA, MA, MN, NJ, PA, RI); Ethylbenzene (CA, MA, MN, NJ, PA, RI); Xylene (CA, MA, MN, NJ, PA, RI).

International Information:

WHMIS information: This product is a WHMIS Controlled Product. It meets one or more of the criteria for a controlled product provided in Part IV of the Canadian Controlled Products Regulations (CPR). Refer to Section 2 for a WHMIS Classification for this product.

Canadian Environmental Protection Act (CEPA): Mixture. All components of this product are on the Canadian DSL list.

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and this MSDS contains all the information required by the CPR.

COSMOFEN 345 ADHESIVE

MSDS Preparation Date (dd/mm/yyyy): 01/03/2010

Page 7 of 8

SECTION 16 - OTHER INFORMATION

HMIS Rating : * - Chronic hazard 0 - Minimal 1 - Slight 2 - Moderate 3 - Serious
Health: *2 *Flammability:* 3 *Reactivity:* 1

Legend : ACGIH: American Conference of Governmental Industrial Hygienists
CA: California
CAS: Chemical Abstract Services
CERCLA: Comprehensive Environmental Response, Compensation, and Liability Act of 1980
CFR: Code of Federal Regulations
CNS: Central Nervous System
DOT: Department of Transportation
DSL: Domestic Substances List
EPA: Environmental Protection Agency
HMIS: Hazardous Materials Identification System
HSDB: Hazardous Substances Data Bank
IARC: International Agency for Research on Cancer
Inh: Inhalation
LC: Lethal Concentration
LD: Lethal Dose
MA: Massachusetts
MN: Minnesota
N/Ap: Not Applicable
N/Av: Not Available
NFPA: National Fire Protection Association
NIOSH: National Institute of Occupational Safety and Health
NJ: New Jersey
NTP: National Toxicology Program
OSHA: Occupational Safety and Health Administration
PA: Pennsylvania
PEL: Permissible exposure limit
RCRA: Resource Conservation and Recovery Act
RI: Rhode Island
RTECS: Registry of Toxic Effects of Chemical Substances
SARA: Superfund Amendments and Reauthorization Act
STEL: Short Term Exposure Limit
TDG: Canadian Transportation of Dangerous Goods Act & Regulations
TLV: Threshold Limit Values
TSCA: Toxic Substance Control Act
TWA: Time Weighted Average
WHMIS: Workplace Hazardous Materials Identification System

References : 1. ACGIH, Threshold Limit Values and Biological Exposure Indices for 2009.
2. International Agency for Research on Cancer Monographs, searched 2010.
3. Canadian Centre for Occupational Health and Safety, CCIInfoWeb databases, 2010 (Chempendium, HSDB, RTECs).
4. Material Safety Data Sheet from manufacturer.
5. US EPA Title III List of Lists October 2006 version.
6. California Proposition 65 List February 5, 2010 version.


Prepared for:

Ferco Ferrures de bâtiment
2000, Rue Berlier
Laval, Qué (Canada), H7L 4S4
Please direct all inquiries to Ferco Ferrures de bâtiment.

COSMOFEN 345 ADHESIVE

MSDS Preparation Date (dd/mm/yyyy): 01/03/2010

Page 8 of 8

<p>Prepared by: ICC The Compliance Center Inc. http://www.thecompliancecenter.com</p>	 <p>The Compliance Center Inc. HAZARDOUS MATERIALS REGULATIONS SPECIALISTS</p>
---	---

DISCLAIMER OF LIABILITY

This Material Safety Data Sheet was prepared by ICC The Compliance Center Inc using information provided by / obtained from Ferro Ferrures de bâtiment and CCOHS' Web Information Service. The information in the Material Safety Data Sheet is offered for your consideration and guidance when exposed to this product. ICC The Compliance Center Inc and Ferro Ferrures de bâtiment expressly disclaim all expressed or implied warranties and assume no responsibilities for the accuracy or completeness of the data contained herein. The data in this MSDS does not apply to use with any other product or in any other process.

This Material Safety Data Sheet may not be changed, or altered in any way without the expressed knowledge and permission of ICC The Compliance Center Inc and Ferro Ferrures de bâtiment.

Preparation Date (dd/mm/yyyy)

: 01/03/2010

END OF DOCUMENT